Campus: Los Angeles

Building Name: Campbell-AAP

CAAN ID: 4294

Auxiliary Building ID: 4294.1



Date: 12/18/2020

FORM 1

CERTIFICATE OF SEISMIC PERFORMANCE LEVEL

☑ UC-Designed & Constructed Facility

Campus-Acquired or Leased Facility

BUILDING DATA

Building Name: Campbell - AAP Addition

Address: 335 Portola Plaza, Los Angeles, CA 90095

Site location coordinates: Latitude 34.07369 Longitudinal -118.44128

UCOP SEISMIC PERFORMANCE LEVEL (OR "RATING"): IV

ASCE 41-17 Model Building Type:

a. Longitudinal Direction: C2a, Concrete Shear Walls w/Flexible Diaphragms

b. Transverse Direction: S2, Steel Braced Frames w/Flexible Diaphragms (Special Concentric) &

C2a, Concrete Shear Walls w/Flexible Diaphragms

Gross Square Footage: 2,030 sf Number of stories *above* grade: 1

Number of basement stories below grade: N/A

Year Original Building was Constructed: 2013

Original Building Design Code & Year: 2010 CBC (1997 UBC) Retrofit Building Design Code & Code (if applicable): N/A

SITE INFORMATION

Site Class: D Basis: Geotechnologies, Inc. (20488), 3/22/2013

Geologic Hazards:

Fault Rupture: No Basis: Geotech Investigation, see above Liquefaction: No Basis: Geotech Investigation, see above Landslide: No Basis: Geotech Investigation, see above

ATTACHMENT

Original Structural Drawings: Campbell Hall – AAP Addition and Renovation, Nabih Youssef Assoc.

(12321.00), 10/18/2013 As-Built

Seismic Evaluation: N/A

Retrofit Structural Drawings: N/A

Campus: Los Angeles

Building Name: Campbell-AAP

CAAN ID: 4294

Auxiliary Building ID: 4294.1



Date: 12/18/2020

CERTIFICATION & PRESUMPTIVE RATING VERIFICATION STATEMENT

I, Nabih Youssef, a California-licensed structural engineer, am responsible for the completion of this certificate, and I have no ownership interest in the property identified above. My scope of review to support the completion of this certificate included both of the following ("No" responses must include an explanation):

an explanation).
 a) the review of structural drawings indicating that they are as-built or record drawings, or that they otherwise are the basis for the construction of the building: ✓ Yes □ No b) visiting the building to verify the observable existing conditions are reasonably consistent with those shown on the structural drawings: ✓ Yes □ No
Based on my review, I have verified that the UCOP Seismic Performance Level (SPL) is presumptively permitted by the following UC Seismic Program Guidebook provision (choose one of the following):
☑ 1) Contract documents indicate that the original design and construction of the aforementioned building is in accordance with the benchmark design code year (or later) building code seismic design provisions for UBC or IBC listed in Table 1 below.
\square 2) The existing SPL rating is based on an acceptable basis of seismic evaluation completed in 2006 or later.
□ 3) Contract documents indicate that a comprehensive ¹ building seismic retrofit design was fully-constructed with an engineered design based on the 1997 UBC/1998 <i>or later</i> CBC, and (choose one of the following):
□ the retrofit project was completed by the UC campus. Further, the design was based on ground motion parameters, at a minimum, corresponding to BSE-1E (or BSE-R) and BSE-2E (or BSE-C) as defined in ASCE 41, or the full design basis ground motion required in the 1997 UBC/1998 CBC <i>or later</i> for EXISTING buildings, and is presumptively assigned an SPL rating of IV.
 □ the retrofit project was completed by the UC campus. Further, the design was based on ground motion parameters, at a minimum, corresponding to BSE-1 (or BSE-1N) and BSE-2 (or BSE-2N) as defined in ASCE 41, or the full design basis ground motion required in the 1997 UBC/1998 or later CBC for NEW buildings, and is presumptively assigned an SPL rating of III. □ the retrofit project was not completed by the UC campus following UC policies, and is presumptively assigned an SPL rating of IV.

¹ A comprehensive retrofit addresses the entire building structural system as indicated by the associated seismic evaluation, as opposed to addressing selective portions of the structural system.

Campus: Los Angeles

Building Name: Campbell-AAP

CAAN ID: 4294

Auxiliary Building ID: 4294.1



Date: 12/18/2020

CERTIFICATION SIGNATURE

AFFIX	SEAL	HERE
-------	------	------

Nabih Youssef	Principal	
Print Name	Title	PROFESSIONAL
S2026	9/30/2021	(5 x 5. 6. 19 9 9)
CA Professional Registration No.	License Expiration Date	Habin Journel
- Statist Churses	12/18/2020	* Exp. 9/30/21 * STAUCTURA FOR CALIFORNIA
Signature	Date	OF CALL
Nabih Youssef Associates, (213) 362 550 S. Hope St., Suite 1700, Los Ang		

Firm Name, Phone Number, and Address

Table 1: Benchmark Building Codes and Standards

	Building Seismic	Building Seismic Design Provisions	
Building Type ^{a,b}	UBC	IBC	
Wood frame, wood shear panels (Types W1 and W2)	1976	2000	
Wood frame, wood shear panels (Type W1a)	1976	2000	
Steel moment-resisting frame (Types S1 and S1a)	1997	2000	
Steel concentrically braced frame (Types S2 and S2a)	1997	2000	
Steel eccentrically braced frame (Types S2 and S2a)	1988 ^g	2000	
Buckling-restrained braced frame (Types S2 and S2a)	f	2006	
Metal building frames (Type S3)	f	2000	
Steel frame with concrete shear walls (Type S4)	1994	2000	
Steel frame with URM infill (Types S5 and S5a)	f	2000	
Steel plate shear wall (Type S6)	f	2006	
Cold-formed steel light-frame construction—shear wall system (Type CFS1)	1997 ^h	2000	
Cold-formed steel light-frame construction—strap-braced wall system (Type CFS2)	f	2003	
Reinforced concrete moment-resisting frame (Type C1) ⁱ	1994	2000	
Reinforced concrete shear walls (Types C2 and C2a)	1994	2000	
Concrete frame with URM infill (Types C3 and C3a)	f	f	
Tilt-up concrete (Types PC1 and PC1a)	1997	2000	
Precast concrete frame (Types PC2 and PC2a)	f	2000	
Reinforced masonry (Type RM1)	1997	2000	
Reinforced masonry (Type RM2)	1994	2000	
Unreinforced masonry (Type URM)	f	f	
Unreinforced masonry (Type URMa)	f	f	
Seismic isolation or passive dissipation	1991	2000	

Note: This table has been adapted from ASCE 41-17 Table 3-2. Benchmark Building Codes and Standards for Life Safety Structural Performed at BSE-1E.

Note: UBC = Uniform Building Code. IBC = International Building Code.

 $^{^{\}rm a}$ Building type refers to one of the common building types defined in Table 3-1 of ASCE 41-17.

^b Buildings on hillside sites shall not be considered Benchmark Buildings.

^c not used

 $^{^{\}it d}$ not used

e not used

^f No benchmark year; buildings shall be evaluated in accordance with Section III.J.

⁹ Steel eccentrically braced frames with links adjacent to columns shall comply with the 1994 UBC Emergency Provisions, published September/October 1994, or subsequent requirements.

 $^{^{\}it h}$ Cold-formed steel shear walls with wood structural panels only.

¹ Flat slab concrete moment frames shall not be considered Benchmark Buildings.