Campus: UCLA - Off Campus

Building Name: CAAN ID:



Auxiliary Building ID:

FORM 1 CERTIFICATE OF SEISMIC PERFORMANCE LEVEL

UC-Designed & Constructed Facility

□ Campus-Acquired or Leased Facility

BUILDING DATA

Building Name: MPTF Saban Center

Address: 23388 Mulholland Drive Woodland Hills, CA 91364

Site location coordinates: Latitude 34.15472 Longitudinal -118.63441

UCOP SEISMIC PERFORMANCE LEVEL (OR "RATING"): IV

ASCE 41-17 Model Building Type:

a. Longitudinal Direction: S1, Steel Moment Frames w/Stiff Diaphragms &

RM2, Reinforced Bearing Masonry Walls w/Stiff Diaphragms

b. Transverse Direction: S1, Steel Moment Frames w/Stiff Diaphragms &

RM2, Reinforced Bearing Masonry Walls w/Stiff Diaphragms

Gross Square Footage:

Number of stories above grade: 2

Number of basement stories below grade: N/A

Year Original Building was Constructed: 2007

Original Building Design Code & Year: 2002 LABC – 1997 UBC Retrofit Building Design Code & Code (if applicable): N/A

SITE INFORMATION

Site Class: D Basis: Default

Geologic Hazards:

Fault Rupture: No Basis: { }
Liquefaction: No Basis: { }
Landslide: No Basis: { }

ATTACHMENT

Original Structural Drawings: (Saban Center for Health & Wellness, KPFF, 2/15/2006, S1.1) or

Seismic Evaluation: N/A

Retrofit Structural Drawings: N/A

Date: 12/14/2020

Campus: UCLA – Off Campus

Building Name: CAAN ID:



Auxiliary Building ID:

CERTIFICATION & PRESUMPTIVE RATING VERIFICATION STATEMENT

I, Nabih Youssef, a California-licensed structural engineer, am responsible for the completion of this certificate, and I have no ownership interest in the property identified above. My scope of review to support the completion of this certificate included both of the following ("No" responses must include an explanation):

an explanation):
 a) the review of structural drawings indicating that they are as-built or record drawings, or that the otherwise are the basis for the construction of the building: ✓ Yes □ No b) visiting the building to verify the observable existing conditions are reasonably consistent with those shown on the structural drawings: ✓ Yes □ No
Based on my review, I have verified that the UCOP Seismic Performance Level (SPL) is presumptively permitted by the following UC Seismic Program Guidebook provision (choose one of the following):
☑ 1) Contract documents indicate that the original design and construction of the aforementioned building is in accordance with the benchmark design code year (or later) building code seismic design provisions for UBC or IBC listed in Table 1 below.
\square 2) The existing SPL rating is based on an acceptable basis of seismic evaluation completed in 2006 o later.
□ 3) Contract documents indicate that a comprehensive building seismic retrofit design was fully-constructed with an engineered design based on the 1997 UBC/1998 <i>or later</i> CBC, and (choose one of the following):
□ the retrofit project was completed by the UC campus. Further, the design was based on ground motion parameters, at a minimum, corresponding to BSE-1E (or BSE-R) and BSE-2E (or BSE-C) as defined in ASCE 41, or the full design basis ground motion required in the 1997 UBC/1998 CBC <i>or later</i> for EXISTING buildings, and is presumptively assigned an SPL rating of IV. □ the retrofit project was completed by the UC campus. Further, the design was based on ground motion parameters, at a minimum, corresponding to BSE-1 (or BSE-1N) and BSE-2 (or BSE-2N) as defined in ASCE 41, or the full design basis ground motion required in the 1997 UBC/1998 <i>or later</i> CBC for NEW buildings, and is presumptively assigned an SPL rating of III. □ the retrofit project was not completed by the UC campus following UC policies, and is presumptively assigned an SPL rating of IV.

Date: 12/14/2020

¹ A comprehensive retrofit addresses the entire building structural system as indicated by the associated seismic evaluation, as opposed to addressing selective portions of the structural system.

Campus: UCLA - Off Campus

Building Name: CAAN ID:



Auxiliary Building ID:

CERTIFICATION SIGNATURE

AFFIX SEAL HERE

Date: 12/14/2020

Nabih Youssef	Principal	
Print Name	Title	OROFESS/ON
S2026	9/30/2021	F. G. YOUR
CA Professional Registration No.	License Expiration Date	Habin Journel
- Stabit Churses	12/14/2020	* Exp. 9/30/21 *
Signature	Date	OF CALIFOR
Nabih Youssef Associates, (213) 362 550 S. Hope St., Suite 1700, Los Ang		

Table 1: Benchmark Building Codes and Standards

Firm Name, Phone Number, and Address

Bu		uilding Seismic Design Provisions	
Building Type ^{a,b}	UBC	IBC	
Wood frame, wood shear panels (Types W1 and W2)	1976	2000	
Wood frame, wood shear panels (Type W1a)	1976	2000	
Steel moment-resisting frame (Types S1 and S1a)	1997	2000	
Steel concentrically braced frame (Types S2 and S2a)	1997	2000	
Steel eccentrically braced frame (Types S2 and S2a)	1988 ^{<i>g</i>}	2000	
Buckling-restrained braced frame (Types S2 and S2a)	f	2006	
Metal building frames (Type S3)	f	2000	
Steel frame with concrete shear walls (Type S4)	1994	2000	
Steel frame with URM infill (Types S5 and S5a)	f	2000	
Steel plate shear wall (Type S6)	f	2006	
Cold-formed steel light-frame construction—shear wall system (Type CFS1)	1997 ^h	2000	
Cold-formed steel light-frame construction—strap-braced wall system (Type CFS2)	f	2003	
Reinforced concrete moment-resisting frame (Type C1) ⁱ	1994	2000	
Reinforced concrete shear walls (Types C2 and C2a)	1994	2000	
Concrete frame with URM infill (Types C3 and C3a)	f	f	
Tilt-up concrete (Types PC1 and PC1a)	1997	2000	
Precast concrete frame (Types PC2 and PC2a)	f	2000	
Reinforced masonry (Type RM1)	1997	2000	
Reinforced masonry (Type RM2)	1994	2000	
Unreinforced masonry (Type URM)	f	f	
Unreinforced masonry (Type URMa)	f	f	
Seismic isolation or passive dissipation	1991	2000	

Note: This table has been adapted from ASCE 41-17 Table 3-2. Benchmark Building Codes and Standards for Life Safety Structural Performed at BSE-1E.

Note: UBC = Uniform Building Code. IBC = International Building Code.

 $^{^{\}rm a}$ Building type refers to one of the common building types defined in Table 3-1 of ASCE 41-17.

^b Buildings on hillside sites shall not be considered Benchmark Buildings.

 $^{^{\}it c}$ not used

^d not used

e not used

 $[\]sp f$ No benchmark year; buildings shall be evaluated in accordance with Section III.J.

^g Steel eccentrically braced frames with links adjacent to columns shall comply with the 1994 UBC Emergency Provisions, published September/October 1994, or subsequent requirements.

 $^{^{\}it h}$ Cold-formed steel shear walls with wood structural panels only.

¹ Flat slab concrete moment frames shall not be considered Benchmark Buildings.